

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For industrial and professional use only.
- · Trade name: B72 Acrylic Adhesive
- · Article number: 8627
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture Surface Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

HMG PAINTS LIMITED

Riverside Works,

Collyhurst Road,

Collyhurst,

Manchester,

M40 7RU

UNITED KINGDOM

TEL: +44 (0)161 205 7631

EMAIL: sales@hmgpaint.com

- · Further information obtainable from: sales@hmgpaint.com
- · 1.4 Emergency telephone number: +44 (0)161 205 7631 (business hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

moking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

Trade name: B72 Acrylic Adhesive

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	propan-2-one Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	>50-≤100%
CAS: 9004-70-0 EC number: 682-719-5	Nitrocellulose (12.3% N) 	>2.5-≤10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-XXXX	propan-2-ol Flam. Liq. 2, H225; \$\frac{1}{4}\$ Eye Irrit. 2, H319; STOT SE 3, H336	>1-≤2.5%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

GE

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

Trade name: B72 Acrylic Adhesive

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

Store in cool, dry conditions in well sealed receptacles.

186 mg/day (Ind)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredien	ts with l	imit values that require monitoring at the workplace:
67-64-1 p	ropan-2	one
		value: 3620 mg/m³, 1500 ppm alue: 1210 mg/m³, 500 ppm
67-63-0 p	ropan-2	-ol
WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm		
DNELs		
67-64-1 p	ropan-2	one
Oral	DNEL	62 mg/day (Con)
Dermal	DNEL	62 mg/day (Con)

(Contd. on page 4)

Version number: 1.08 Revision: 15.01.2024 Printing date 15.01.2024

Trade name: B72 Acrylic Adhesive

			(Contd. of page 3
Iı	nhalative	DNEL	$200 \text{ mg/m}^3 \text{ (Con)}$
			$1,210 \text{ mg/m}^3 \text{ (Ind)}$
6	67-63-0 pr	opan-2-	ol
C	Oral	DNEL	26 mg/day (Con)
L	Dermal	DNEL	319 mg/day (Con) 888 mg/day (Ind)
			888 mg/day (Ind)
Iı	nhalative	DNEL	$89 mg/m^3 (Con)$
			89 mg/m³ (Con) 500 mg/m³ (Ind)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: When spraying the product, use a respiratory protective device.
- · Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties · General Information

· Appearance: Form:

Liquid Colour: Clear

Characteristic · Odour: · Odour threshold: Not determined.

Not determined. · pH-value:

· Change in condition

Undetermined. Melting point/freezing point:

Initial boiling point and boiling range: 56 °C

-17 °C · Flash point:

· Flammability (solid, gas): Highly flammable.

170 °C · Auto-ignition temperature:

Not determined. · Decomposition temperature:

(Contd. on page 5)

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

Trade name: B72 Acrylic Adhesive

	(Contd. of page 4
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	14.3 Vol %
· Vapour pressure at 20 °C:	240 hPa
· Density at 20 °C:	0.932 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	48 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	56.6 %
Solids content:	43.4 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
67-64-1 pr	67-64-1 propan-2-one		
Oral	LD50	5,800 mg/kg (Rat)	
Dermal	LD50	7,400 mg/kg (Rabbit)	
Inhalative	LC50/4 h	76 mg/l (Rat)	
9004-70-0	9004-70-0 Nitrocellulose (12.3% N)		
Oral	LD50	>5,000 mg/kg (Rat)	
67-63-0 pr	67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (Rat)	
Dermal	LD50	13,900 mg/kg (Rab)	

(Contd. on page 6)

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

Trade name: B72 Acrylic Adhesive

(Contd. of page 5)

Inhalative LC50/4 h >25 mg/l (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number	******
· ADR, IMDG, IATA	UN1133
· 14.2 UN proper shipping name	
$\cdot ADR$	1133 ADHESIVES (vapour pressure at 50°C not more than
	110 kPa)
· IMDG, IATA	ADHESIVES

(Contd. on page 7)

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

Trade name: B72 Acrylic Adhesive

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA II· 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): F-E,S-E· EMS Number: · Stowage Category В · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code *Not applicable.* · Transport/Additional information: · Limited quantities (LQ) 5LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E · IMDG 5L· Limited quantities (LQ) Code: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1133 ADHESIVES (VAPOUR PRESSURE AT 50°C · UN "Model Regulation": NOT MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 propan-2-one Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2024 Version number: 1.08 Revision: 15.01.2024

Trade name: B72 Acrylic Adhesive

· Seveso category P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	56.6

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Full text of H-Statements referred to under sections 2 and 3:

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

 $STOT\,SE\,3\colon Specific\ target\ organ\ toxicity\ (single\ exposure)-Category\,3$

· * Data compared to the previous version altered.

GB